

Tiggo Specifications



Powertrain	1.6MT			1.8MT	2.0MT	2.0AT		2.0AWD		
Model type	Standard	Comfortable	Luxury	Standard	Standard	Standard	Comfortable	Standard	Comfortable	Luxury
Measurement & Quality										
Length*Width*Height (mm)	4285*1765*1705			4285*1765*1705	4285*1765*1705	4285*1765*1705		4285*1765*1705		
Wheelbase (mm)	2510			2510	2510	2510		2510		
Turning radius (m)	5.5			5.5	5.5	5.5		5.5		
Weights - curb weight (kg)	1375			1390	1375	1400		1455		
Tyre size	235/60 R16	235/60 R16	215/65 R16	215/65 R16	235/60 R16	215/65 R16	235/60 R16	235/60 R16	215/65 R16	235/60 R16
Engine										
Engine code	ACTECO-SQR481F			ACTECO-SQR481FC	SQR484F	SQR484F		SQR484F		
Engine liters (cc)	1597			1845	1971	1971		1971		
Maximum power (Kw/rpm)	87.5/6150			97/5750	102/5750	102/5750		102/5750		
Maximum torque (Nm/rpm)	147/4300~4500			170/4300~4500	182/4300~4500	182/4300~4500		182/4300~4500		
Engine compression ratio	10.5:1			10.5:1	10:1	10:1		10:1		
Max. speed (km/h)	160			175	170	170		170		
Transmission - number of speeds / type	5MT			5MT	5MT	4AT		5MT		
Fuel tank capacity (l)	57			57	57	57		57		
Emission	EuIII	EuIII	EuIV	EuIII+OBD	EuIV	EuIV	EuIII+OBD	EuIII+OBD	EuIV	EuIII+OBD
Brake, Suspension & Drive mode										
Brake system (Front / Rear)	ventilation discs / discs			ventilation discs / discs	ventilation discs / discs	ventilation discs / discs		ventilation discs / discs		

Tiggo Specifications



Front suspension system	Independent Macpherson strut, with stabilizer, conical variable pitch coil spring and dual-acting tube damper			Independent Macpherson strut, with stabilizer, conical variable pitch coil spring and dual-acting tube damper	Independent Macpherson strut, with stabilizer, conical variable pitch coil spring and dual-acting tube damper	Independent Macpherson strut, with stabilizer, conical variable pitch coil spring and dual-acting tube damper				
Rear suspension system	Longitudinal double trailing arm suspension with cylindrical constant pitch coil spring, dual-acting tube damper and stabilizer			Longitudinal double trailing arm suspension with cylindrical constant pitch coil spring, dual-acting tube damper and stabilizer	Longitudinal double trailing arm suspension with cylindrical constant pitch coil spring, dual-acting tube damper and stabilizer	Longitudinal double trailing arm suspension with cylindrical constant pitch coil spring, dual-acting tube damper and stabilizer		Longitudinal double trailing arm suspension with cylindrical constant pitch coil spring, dual-acting tube damper and stabilizer		
Drive wheels	Front			Front	Front	Front		AWD		
Exterior										
Aluminium alloy wheels	•	•	•	•	•	•	•	•	•	•
Color-keyed electric rearview mirror with heating	•	•	•	•	•	•	•	•	•	•
Rear windshield wiper	•	•	•	•	•	•	•	•	•	•
Sunroof		•	•			•	•		•	
Interior										
Gray upholstery	•	•			•					
Beige upholstery			•	•		•	•	•	•	•

